



VIDEO SPLITTER MODULE **5310-T82**

APPLICATION

- This module distributes video signal to 8 television outlets through out the home.

FEATURES

- Easily be installed with nut screwed. Just tighten the nut to the port of the splitter and the installation is completed.
- Transmission Performance up to 2G.
- Available in Metal and Plastic Bracket.
- Available in 4/6/8 television outlets for Distributes Video Signal.

TRANSMISSION PERFORMANCE

| Bandwidth(MHz) | 5-47 | 47-1000 | 1000-1750 | 1750-2050 | 2050-2300 |
|-----------------------------|------|---------|-----------|-----------|-----------|
| Insertion Loss(dB) Max. | 16.5 | 16.5 | 17.5 | 20 | 21 |
| Input Return Loss(dB) Min. | 7 | 8 | 8 | 8 | 8 |
| Output Return Loss(dB) Min. | 3.5 | 8 | 8 | 8 | 8 |
| Isolation(dB) Min. | 13 | 18 | 18 | 18 | 18 |

PHYSICAL SPECIFICATIONS

- UL 1863 safety listed.
- Bracket : Cold Rolled Steel.
- Dimensions : 164.4mm(W) x 58.0mm(H) x 83.0mm(D).
- Revit pitch : 152.4mm(W), 25.4mm(H).

